



TYPICAL INSTALLATION
Maximum installation distances:
A: Maximum distance 20' (6 m).
B: Maximum height between pump inlet and engine oil sump level, 3' (1 m).

EvacuMaster Used Oil Suction Unit

Single point suction unit for collecting used oil directly from the vehicle's engine using a suction wand inserted into the engine oil dipstick tube. The unit is installed alongside the service bay and provides the cleanest method for used oil collection.

Direct extraction from engine to storage tank eliminates operator contact with used oil and spills. It also eliminates the use of mobile units and drain plug issues.

An air operated pump, specially designed for suction applications, extracts the used oil and pumps it to a remote storage tank. The unit includes an on/off valve, air filter with pressure regulator, vacuum gauge for monitoring unit performance, extra large capacity suction filter, 9' (3 m) suction hose, and complete kit of suction wands and adaptors.

EvacuMaster Used Oil Portable Unit

A portable version of the single point suction unit. The unit is mounted to a 27 gallon tank wit two fixed large wheels with roller bearings and two heavy-duty casters.

The oil is extracted from the dipstick and pumped into the 27 gallon tank. Pressurize the tank for evacuation at 3.5 psi (0.5 bar) maximum.

MARKETS SERVED

- Car and truck dealers
- Service shops
- Quick lubes

FLUIDS HANDLED

- Used oil
- Synthetic and mineral oils



ORDER INFORMATION

Part no.	Description	Service manual
EvacuMaster USED OIL SUCTION UNIT Includes 8 pc wand kit 737 950.300		
379 711	Wall mounted used oil suction unit	SM837 822
379 710	Pedestal mounted used oil suction unit	
EvacuMaster USED OIL PORTABLE UNIT Includes 8 pc wand kit 737 950.300		
379 707	EvacuMaster Portable: A portable version of our single point used fluid suction unit	SM837 822
379 708	EvacuMaster Portable: with drain bowl	
379 712	EvacuMaster Portable: ATF w/ 10 qt transparent chamber	



EvacuMaster WAND KITS Wand and adaptor kit for use with all used oil suction units.

Package Part No.		737 950.300	1928
737 952	Flex-0.23 x 0.15 x 27.55"	1	1
737 953	Flex-0.31 x 0.23 x 27.55"	1	--
737 960	Flex-0.19 x 0.15 x 27.55"	2	1
737 958	Flex-0.23 x 0.15 x 47.24"	1	1
737 959	Flex-0.31 x 0.23 x 47.24"	1	--
737 961	Flex-0.19 x 0.15 x 39.37"	2	2

Recommended Accessories

506 503

20" x 5/8" HP Used Oil suction - Steel Shaft & Swivel
2,000 psi (138 bar)