Cast Iron / Hard chromed steel / Carbon steel / Zinc Plated steel /

417 009



Grease transfer pump for unloading 400 lb drums. Shovel intake design for effective priming even with high viscosity grease.

Pump are available with tube length to fit commercial 400 lb drums. They can be flange cover mounted to 400 lb open drums.

### 41/2" air motor

Mechanically actuated air valve with only three moving parts and no springs. Large effective area for maximum pumping power

### **Efficient air exhaust**

No ice forming, no stalling pump operation

# Long life packings

Anti-corrosion, hardened plunger and cartridge packings assembly designed for low friction.

## High quality materials

Low friction polyurethane seals, hard chromed steel fluid plunger and steel valves for fewer repairs

### **Ductile iron pump body**

For superior properties

### Pump Inlet Valve


Chop-check priming valve, assists the entry of heavy and sticky grease

#### **MARKETS SERVED**

- Mining and construction
- Lube trucks
- · Railroad and mass transit
- Marine
- Industrial

#### **FLUIDS HANDLED**

• Grease up to NLGI-2





#### **TECHNICAL SPECIFICATIONS** 10:1 Pump ratio 30 - 100 psi (2 - 7 bar) Air pressure operating range Maximum fluid outlet pressure 1,000 psi (70 bar) Air motor diameter 4.5" (115 mm) Air motor stroke 4" (100 mm) Delivery at 80 cpm (1) 20 lb/min (9 kg/min) Maximum free flow delivery 75 lb/min (100 psi) Air inlet 1/2" NPT(F) 1" NPT(F) Fluid outlet

853 868

# **ORDER INFORMATION**

(1) Delivery at 60 cycles per minute.

Wetted materials

Manual

**531 011** PM45 10:1 400 lb drum, flange mounted

## Hose Kit High pressure hose connection kit for PumpMaster 45 10:1



539 009	
LP Hose 1/2" x 5'	823
HP Hose 1" x 5'	863
Quick Air Coupler 1/2" NPT(F)	947F08
Quick Air Nipple 1" (M)	946M08

NBR / PTFE / Polyurethane / POM

#### **Drum Cover**



418 026 400 lb l

400 lb Heavy-duty drum cover PM45/60



400 lb Heavy-duty follower plate PM45/60