



413 080

## High Pressure Grease Handles

High pressure grease dispenses handle with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminum with steel insert for high pressure.

Oval gear grease meter for all types of grease, with digital display and ergonomic grip. Progressive opening valve for excellent control of grease delivery. The gun includes inlet z-swivel and outlet hose with Zerk connector.



413 077



413 081



413 082



415 012

## TECHNICAL SPECIFICATIONS

	Metered	Non-Metered
Maximum flow rate	2.2 lb/min (1 Kg/min)	--
Maximum working pressure	7,250 psi (500 bar)	7,250 psi (500 bar)
Inlet	1/4" NPT(F)	1/4" NPT(F)
Outlet	1/8" NPT(F)	1/8" NPT(F)
Accuracy	+/- 2.0%	--
Power Source	2x "AAA" 1.5 Batteries	--
Wetted parts	Aluminum / Stainless Steel	Aluminum / Stainless Steel
Manual	M00091	M00091

### MARKETS SERVED

- Fleet service
- Lube trucks
- Mining equipment maintenance
- Truck dealerships
- Maintenance shops
- Mass transit maintenance
- Railroad

### FLUIDS HANDLED

- Grease

## ORDER INFORMATION

<b>413 077</b>	Grease Control Handle, 3-Jaw Coupler
<b>413 080</b>	Grease Control Handle, 3-Jaw Coupler, Rigid Outlet
<b>413 081</b>	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose
<b>413 082</b>	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose, Z-Swivel
<b>415 012</b>	Grease Control Handle, 3-Jaw Coupler, 18" Steel Braided Hose, Z-Swivel, Electronic Grease Meter